OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION ____35_TOWNSHIP. DATE: 7-16-07 3 PARTY CHIEF: Wilcoxen CREW: -TYPE OF MARKER: Harrison 0 METHOD OF ESTABLISHMENT: ___County: 4-18-00 EDM IN. S.P.C. E ZONE NAD '83 1 NAME: 17023502 514535.1410(m) N: E: 48447.8500(m) NOTE: This corner position represents a title corner and may not necessarily be in the position of the Record corner. 1. 4 W. 71st Street Section Line 7100 N Note: Harrison is in S.most turn lane to I-465 N Bound. 2. 3

71st Street 7100 N

Original post set 1821 by Wm. B. Laughlin with witness: 10" hornbean N 60 E 18 links; 3" dogwood S 30 W 17 links per Marion County Atlas pg. 4. A survey by D.B. Hosbrook 10-15-1852 indicates a rock set with witness: 22" beech N 58 1/2 E 44 links. miller 10-2-48 called 1 1/2" sq. brass plug. Burres 1-26-44 called same. Miller 4-11-75 called the same. Gries 7-11-88 called same. Wilcoxen 10-18-89 called same. Excavated 8-15-90 by Wilcoxen and set Harrison. Re-tied 4-18-00 by Wilcoxen. Re-tied 7-10-07 by Wilcoxen per new road construction.

| REF. | DISTANCE | DESCRIPTION |
|------|----------|---------------------|
| 1. | 152.54 | SF corner of bridge |
| 2. | 166.38' | NF corner of bridge |
| 3. | 82.13' | NW corner of bridge |
| 4. | 56.62' | SW corner of bridge |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |